

Technical Information

- ¹ if stored on vertical position (AA Zone 1).
- ² Immersion in water is not recommended.
- ³ Solar Heat Gain
Coefficient: 0,40 (tested on 3/16" clear single glazed glass)
Percent Reduction of Heat Transfer: 52%
Visible Light Transmittance: 0.274
Solar Transmittance: 0.251
Ultraviolet Blockage: 0.917

- **Guidelines:**

Glass surfaces must be cleaned with an alcohol free product prior to application.

Liner must be removed from glass surface at 90°.

Low/high temperatures and solvent based inks may impact the clean removability of the film.

- For further information please refer to our Technical Bulletin or contact us

Film	200μ black/white composite micro perforated PVC vinyl
Adhesive	25μ clear removable solvent based pressure sensitive adhesive
Liner	178μ PET
Standard Width	137,2cm
Standard Length	30,48ml
Expected Lifetime Exterior ¹	3 years
Clean Removability	6 months. Adhesion may increase with time
Storage Stability ¹	1 year shelf life if stored at 21° and 50% relative humidity
Minimum Application Temperature	+6° C
Service Temperature Range	-17° C to 62° C
Dimensional Stability	Good
Solvent Resistance	Good
Humidity Resistance	Fair
Water Resistance ²	Fair
Certifications ³	Heat & Light Control

Warranty

Information provided above is based upon tests that are believed to be reliable. There are intended as a source of information and do not constitute a warranty. ClearFocus takes great pride in ensuring tight quality control and we warranty our products to be free from visible defects at the time of sale. Any material showing visual defect at the time of sale will be replaced without charge. Our liability is limited to the costs of material and ClearFocus shall in no circumstances cover expenses associated to the transformation and/or application of its products.