

Premium Self-Adhesive Perforated PET (PVC-Free)

Key Features

- Co- laminated white/black PET
- Semi-Gloss white smooth finish
- Open area: 35%
- Printable area: 65%
- Perforation diameter: 1,5mm

 **PVC-Free**

Product Features and Applications

- 100µ perforated PET with a printable top coat for (Eco)-Solvent and Latex inks.
- Available with a double PET liner for UV printing

Applications

- PREMIUM PET for mid to long term exterior-mount applications on glass surfaces for retail and commercial signage, design and architectural applications
- Apply to cleaned glass surface
- Application on non-glass transparent surfaces such as (but not limited to) polycarbonate or PMAA is possible but not recommended and must be tested.
- The nature of this product makes it unsuitable for applications on curved surfaces.

Key Benefits

- Dimensional Stability: Excellent
- Combinations of print & CAD
- Durability: 5 years outdoor
- Printable with Latex, Solvent, Eco-solvent and UV inks

Benefits

- European made solution for better quality control and carbon footprint
- Innovative non PVC solution (recyclability under test)
- The rigidity of this product makes the application very easy and GreenVue stands on your window with superb lay flatness
- The 65/35 perforation pattern is specifically designed to provide a strong visual impact while ensuring good visibility from the inside
- GreenVue is compatible with eco-solvent, latex, UV printers and inks
- Always test your printing/ink combination prior to commercial use.

Premium Self-Adhesive Perforated PET (PVC-Free)

Technical Information

- 1 if stored on vertical position (AA Zone 1)

Guidelines:

- Lamination is recommended if application requests good visibility in a rainy environment
- We recommend a minimum of 24 hours between printing and application of the film.
- Not suitable for wet application
- Glass surfaces must be cleaned with an alcohol free product prior to application
- Exceptional dimensional stability and tensile strength

Surface	100µ white/black co-laminated PET
Finish	Semi-gloss Top Coating for Digital Printing
Adhesive	Transparent
Liner	2 side PE coated Universal liner
Perforation Pattern	65/35
Standard Width	1,372 m
Standard Length	50 ml
Expected Lifetime Interior ¹	5 years
Clean Removability	1 year
Storage Stability ¹	24 months if stored at 21° and 50% relative humidity
Application Temperature Range	≥ 6° C
Service Temperature Range	-40° C to 80° C
Storage Temperature	+10° C to 20° C
Dimensional Stability	Excellent
Printability	Latex, Eco-Solvent, UV

Warranty

Information provided above is based upon tests that are believed to be reliable. They are intended as a source of information and do not constitute a warranty. Clear Focus Europe takes great pride in ensuring tight quality control and we warrant our products to be free from visible defects at the time of sale. Any material showing visual defect at the time of sale will be replaced without charge. Our liability is limited of the costs of material and Clear Focus Europe shall in no circumstances cover expenses associated to the transformation and/or application of its products.